

89MQ **ключ накидной односторонний, диэлектрический**

EN 60900


| art. | art. | mm | L mm | D mm | A mm | S mm | g |
|-----------|---------|----|------|------|------|------|-----|
| 000890110 | 89MQ 10 | 10 | 170 | 19 | 17 | 9,5 | 75 |
| 000890111 | 89MQ 11 | 11 | 180 | 20,3 | 17,5 | 10 | 74 |
| 000890112 | 89MQ 12 | 12 | 190 | 21,8 | 21 | 10 | 132 |
| 000890113 | 89MQ 13 | 13 | 195 | 23 | 21 | 10,5 | 106 |
| 000890114 | 89MQ 14 | 14 | 200 | 24,6 | 21,2 | 11 | 168 |
| 000890115 | 89MQ 15 | 15 | 210 | 25,5 | 21 | 10,8 | 161 |
| 000890117 | 89MQ 17 | 17 | 218 | 30 | 22 | 13 | 209 |
| 000890119 | 89MQ 19 | 19 | 240 | 31,5 | 25 | 13 | 307 |
| 000890122 | 89MQ 22 | 22 | 255 | 35,5 | 28 | 15 | 350 |
| 000890124 | 89MQ 24 | 24 | 280 | 39 | 29 | 16 | 425 |

